

**CHAMPION<sup>®</sup>**  
**STERLING**



**Sales &  
Rental  
Catalogue**

**CHAMPION STERLING MANUFACTURING PVT. LTD.**

## SINGLE WIDTH MONKEY LADDER



- Fully certified to the very latest TUV.
- Confirms to the requirements of the 3T erection and dismantling method as set out by the HSE (Health & safety Executive).
- Available in 20 working heights for each of the different widths and Lengths, from 1.2 m to 22 m (Platform height) in 0.5m increments.
- Weight rating 950 kg less tower self weight.
- Frame Sections available in 850mm and 1450mm widths and 1m, 1.5m and 2m heights.
- Fully welded Ladder incorporated into frame.
- Fitted with Dual locking castors individually certified to 700KG. Tower base plates are available as an alternative.
- Tube to tube joints makes frames lighter.

## FOLDOUT TOWERS



- Folding base unit suitable for single person assembly.
- 240mm rung spacing.
- Maximum single platform safe working load of 275kg, the same as our industrial towers.
- Colour coded bracing system with a large coloured trigger for easier identification and operation.
- Folding toeboard for quick & east installation.
- Platform height up to 13m with a safe working height of 11m.
- Fits easily into most small vans or estate cars.
- 7 platform heights (using extra components)
- Adjustable legs and castor are available.
- Crimped spigots for easy assembly dismatch.
- Comes with a 1 year warranty from manufacturing defects.

## STAIRWAY TOWER

- Tube to tube joints makes frames lighter.
- Integral with 240mm rung spacing.
- Conforms to the requirements of the 3T erection and dismantling method.
- Available in 23 working heights for each of the 4 different Widths and Lengths, from 1.2m to 12.2m (platform height).
- Weight rating 950kg less tower self weight.
- Frame Section available in 850mm and 1450mm widths and 1m, 1.5m and 2m Heights.
- Fully welded Ladder incorporated into frame.
- Fitted with single locking castors individually certified to 700KG. Tower base plates are available as an alternative.
- Safe working load of 275kg. per platform.
- Crimped Spigots for easy assembly/dismatching.



## INDUSTRIAL TOWER

- Manufactured under ISO 9001:2015.
- Made from 2.5mm aluminium.
- Folds away flat for ease of storage & transport.
- Fits through standard doorways & corridors at 85mm wide.
- Folding base unit suitable for single person assembly.
- Integral with 240mm rung spacing.
- Maximum platform safe working load of 275kg, per platform the same as our industrial towers.
- Colour coded bracing system with a large coloured trigger for easier identification and operation.
- Folding toeboard for quick & east installation.
- Fits easily into most small vans or estate cars.
- Adjustable legs and castor (220mm) are available.
- Crimped spigots for easy assembly/dismatch.
- Comes with a 1 year warranty from manufacturing defects.



## ALUMINIUM SCAFFOLDING CANTILEVER



- Manufactured under ISO 9001:2015.
- Made from the highest grade aluminium 6082 T6.
- Ideal for high spaces and landing areas on stairwells.
- Width of cantilever set:0.85m.
- Length of cantilever set: 1.80m.
- For doubling or tripling the working area.
- For working above impediments that would make the space under the platform narrower.
- For creating a number of workstations on a single scaffold.

## STAIRWELL TOWERS

- Manufactured under ISO 9001:2015.
- Made from the highest grade aluminium 6082 T6.
- Ideal for tight spaces and landing areas on stairwells.
- Removable Ladder for ease of access.
- 240mm Rung pitching.
- Single Piece folding toeboard.
- 850mm x 1.8m Trapdoor platform a slip resistant deck, self closing trapdoor and windlock.
- 2 stabiliser options available (standard or wall prop).
- Overall width 760mm.
- Adjustable legs and base plates.
- Colour coded brace hooks.
- Crimped spigots for easy assembly/dismant.
- Comes with a 1 year warranty for Manufacturing defects.



## FRP SINGLE WIDTH SCAFFOLDING



- Electric shock proof non-conductive for use near electrical risks.
- Non-corrosive so suitable near chemical & electric Industry.
- Easily transported and assembled like a aluminium mobile tower.
- Clean to handle thus perfect for hygiene conscious environments.
- Comes with scaffolding dimension 0.85 x 1.8m.
- Corrosion free, non-conductive and clean to handle, these non-conductive towers for chemical hazard electrical risk.
- Colour coded brace hook.

## FRP DOUBLE WIDTH SCAFFOLDING



- Non-corrosive so suitable near chemical & electric Industry.
- Easily transported and assembled like a aluminium mobile tower.
- Corrosion free, non-conductive and clean to handle, these non-conductive towers for chemical hazard electrical risk.
- Comes with scaffolding dimension 1.45 x 1.8m.
- Electric shock proof non-conductive for use near electrical risks.
- Clean to handle thus perfect for hygiene conscious environments.
- Colour coded brace hook.

## FRP LADDER

- Integrated tool tray for holding tools whilst you work.
- Extra bracing at the foot to enhance support, Semi tubular rivets provide rigid fixing.
- H-spreaders offer single handed operation and provide strength and stability.
- Slip-resistant treads, 150kg load capacity suitable for heavy trade use.
- Non-conductive fibreglass tiles, ideal for working around electricity.
- Available in 3 steps to 12 steps.



## MULTIPURPOSE LADDER

- Light weight, versatile and compact.
- Can be used on stairs.
- Standard Ladder outside width: 420mm & pitch 280mm.
- Upto 1000mm wide base leg.
- When folded the ladder will fit into the boot of car.



Self Support



A-Type



Work Platform



**CHAMPION<sup>®</sup>**  
**STERLING**

## OUR PRESENCE



**CHAMPION<sup>®</sup>**  
**STERLING**

**CHAMPION STERLING MANUFACTURING PVT. LTD.**

**Reg. Office:** 2309, Spira Tower, Super Nova, Sector 94, Noida - 201313 (U.P.)  
**Works:** D-11/8, UPSIDC Industrial Area, Site-5, Kasna, Greater Noida - 201306 (U.P.)  
**Phone:** +91- 9871940727 | **Email:** contact@championsterling.com

**web:** [www.championsterling.com](http://www.championsterling.com)